



HOLE	DIA.	QTY.	APPLICATION
A	0.625	4	FLOOR MOUNTING
B	1.313	6	PRE-FAB CONDUIT KNOCKOUT FOR 1in CABLE (BOTH SIDES)

STANDARD PRE-FAB CONDUIT KNOCKOUTS ARE SHOWN. IF ADDITIONAL CONDUIT ENTRANCES ARE REQUIRED BY USER, ENCLOSURE SHOULD BE FIELD-MODIFIED BY INSTALLER.

NOTES:

- 1) DETAIL VIEW OF INSTRUMENT PANEL IS FEATURED ON DRAWING JE0260-XX.
- 2) BATTERY CHARGER SHIPPING WEIGHT: APPROXIMATELY (710-1100) lbs.
- 3) ENCLOSURE IS A NEMA-1 TYPE CABINET WITHOUT GASKETS.
- 4) ALLOW 12in (305mm) OF FREE AIR IN FRONT AND ON TOP OF CABINET FOR VENTILATION.
- 5) BOTTOM CONDUIT ENTRY IS POSSIBLE, THROUGH EXPANDED METAL UNDERSIDE.

REV	ECN No	DATE	APP	THIRD ANGLE PROJECTION		HINDLEPOWER		1075 Saint John Street Easton, PA 18042-6661 PH 610-330-9000 FAX 610-330-8510 www.hindlepowerinc.com	
3	E1385	102403		DRAWN BY	PAC	051194	TITLE SCR/SCRF SERIES BATTERY CHARGER OUTLINE: NEMA-1 STYLE-4 ENCLOSURE		
2	E1150	022603	MCT	APPROVED	WAH	051194	DRAWING No		REV 3
1	E0511	072401	MCT	UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES. TOLERANCES ARE:		JE0464-03		B	
0	11001	051194	WAH	SCALE	NTS	PART No	JE0464-03	SHEET	1 OF 1