



NOTES:

- * STEERING DIODES LINK TWO (2) BATTERY CHARGER DC OUTPUT BUSES TO COMMON LOAD WITHOUT LINKING BATTERY BANKS TOGETHER, SEE OPERATING INSTRUCTIONS (JA5065-00)
- * STEERING DIODES AND I/O TERMINALS (TB#) ARE CONNECTED WITH FLAME-RETARDANT BLACK SWITCHBOARD INSULATION SYSTEM (SIS) TYPE WIRING, IDENTIFIED ON EACH END WITH NUMBER-CODED MARKERS
- * USER CONNECTIONS:
THREE (3) CU-AL COMPRESSION LUGS WILL ACCEPT #14-1/0 AWG USER WIRING
GROUND (DOOR & CHASSIS)
TWO (2) #10 ZPS STUD TERMINALS

PART No.	VOLTAGE RATING	CURRENT RATING
EJ5144-20	250 VDC	50 ADC
EJ5144-24	600 VDC	50 ADC

1	24848	040815	THIRD ANGLE PROJECTION	TITLE BEST BATTERY SELECTOR INTERNAL COMPONENT LAYOUT: NEMA-1 STYLE-586 ENCL (50Adc)		
0	23733	052813				
B	-N/A-	-N/A--	UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES. TOLERANCES ARE:	DRAWING No JE5139-00		
A	N/A	093010		SCALE NTS	PART No JE5139-00	SHEET 1 OF 1
REV	ECN No	DATE				