



PROCEDURE / NOTES:

- 1) RACK MUST BE 23in / 584mm EIA TYPE, CAPABLE OF SUPPORTING WEIGHT OF CHARGER PLUS BRACKETS. 19in / 477mm RACK-MOUNTING NOT POSSIBLE WITH STYLE-5054 ENCLOSURE.
- 2) POSITION & MIRROR RACK-MOUNTING BRACKETS ONTO REAR FLANGES OF STYLE-5054 ENCLOSURE AS SHOWN.
 A) USE BOTTOM PAIR OF KEY-HOLE SLOTS ON STYLE-5054 ENCL
 B) USE SECOND-MOST OUTER, OF FIVE (5) HOLES ON BRACKETS

HERE

HERE
- 3) FASTEN BRACKETS TO KEY-HOLE SLOTS USING SUPPLIED 1/4-20 HARDWARE. TORQUE SPECIFICATIONS: 57-77 in-lb
- 4) MOUNT COMPLETE ASSEMBLY (CHARGER PLUS BRACKETS) INTO 21.72in / 552mm RACK OPENING. SECURE TO RACK WITH USER-SUPPLIED HARDWARE.
- 5) SIDE CONDUIT ENTRANCES CLEAR FROM BRACKETS
- 6) IF TWO (2) CHARGERS ARE TO BE MOUNTED INTO RACK, ONE (1) ON TOP OF ANOTHER, ALLOW 6in / 152mm CLEARANCE ON TOP AND BOTTOM FOR VENTING.
- 7) SEE OUTLINE DRAWING (JE5251-00) FOR STANDARD SPECIFICATIONS OF NEMA TYPE-1 STYLE-5054 ENCLOSURE.
- 8) STYLE-5054 23in / 584mm RELAY RACK-MOUNTING ACCESSORY IS MANUFACTURER'S INTERNAL ORDERING PART No E10193-50.

DUAL DIMENSIONS in mm

			<p>THIRD ANGLE PROJECTION</p>			
			DRAWN BY MCR 012519 ELECTRONIC APPROVAL SIGNATURES MAINTAINED BY MFG ECN LOG	TITLE ATevo SERIES BATTERY CHARGER OUTLINE: NEMA-1 STYLE-5054 ENCLOSURE (23in RACK)		
B	-N/A-	051821	UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES. TOLERANCES ARE:	DRAWING No JA0091-50		REV B
A	-N/A-	012519		SCALE NTS		PART No JA0091-50
REV	ECN No	DATE				